





Product Service

# CERTIFICATE

No. Z1 043527 0006 Rev. 00

## Model(s):

1400220 S, 1400221 S, 1400222 S, 1400223 S, 1400224 S, 1400225 S, 1400226 S, 1400226 SCL, 1400227 S, 1400227 SCL, 1400228 S (Kids), 1400229 S (Kids), 1400222H2 S, 1400223H3 S, 1400226H6 S, 1400227H7 S, 1400241 S, 1400242 S, 1400243 S, 1400244 S, 1400261 S, 1400262 S, 1400263 S, 1400264 S, 1400265 S, 1400266 S, 1400268 S (Kids), 1400269 S (Kids)

## Parameters:

| Type:   | Handle length:       | Ø-handle: | Material:      | max. user weight: |
|---|----------------------|-----------|----------------|-------------------|
| <b>Mobile grab rail with vacuum safety indicator</b>                          |                      |           |                |                   |
| 1400220 S   | 110 mm               | 35 mm     | PVC/PA 6.6     | 105 kg            |
| 1400221 S   | 220-345 mm           | 35/24 mm  | PVC/PA 6.6     | 85 kg             |
| 1400222 S   | 340-465 mm           | 35/24 mm  | PVC/PA 6.6     | 85 kg             |
| 1400223 S   | 440-565 mm           | 35/24 mm  | PVC/PA 6.6     | 85 kg             |
| 1400224 S   | 665-790 mm           | 35/24 mm  | PVC/PA 6.6     | 80 kg             |
| 1400225 S   | 210 mm               | 35 mm     | PVC/PA 6.6     | 100 kg            |
| 1400226 S   | 350 mm               | 35 mm     | PVC/PA 6.6     | 95 kg             |
| 1400226 SCL (ChromLook)   | 350 mm               | 35 mm     | PVC/PA 6.6     | 95 kg             |
| 1400227 S   | 650 mm               | 35 mm     | PVC/PA 6.6     | 95 kg             |
| 1400227 SCL (ChromLook)   | 650 mm               | 35 mm     | PVC/PA 6.6     | 95 kg             |
| 1400228 S (Kids)  | 170 mm               | 26 mm     | PVC/PA 6.6     | 75 kg             |
| 1400229 S (Kids)  | 310 mm               | 26 mm     | PVC/PA 6.6     | 75 kg             |
| <b>Mobile angle-adjustable telescopic handle with vacuum safety indicator</b> |                      |           |                |                   |
| 1400222H2 S   | 340-465 / 340-465 mm | 35/24 mm  | PVC/PA 6.6/POM | 85 kg             |
| 1400223H3 S   | 440-565 / 440-565 mm | 35/24 mm  | PVC/PA 6.6/POM | 85 kg             |
| 1400226H6 S   | 350 / 350 mm         | 35 mm     | PVC/PA 6.6/POM | 95 kg             |
| 1400227H7 S   | 650 / 650 mm         | 35 mm     | PVC/PA 6.6/POM | 95 kg             |
| <b>QuattroPlus grab rail with vacuum safety indicator</b>                     |                      |           |                |                   |
| 1400241 S   | 200 - 325 mm         | 35/24 mm  | PVC/PA 6.6/POM | 160 kg            |
| 1400242 S   | 320 - 445 mm         | 35/24 mm  | PVC/PA 6.6/POM | 160 kg            |
| 1400243 S   | 420 - 545 mm         | 35/24 mm  | PVC/PA 6.6/POM | 160 kg            |
| 1400244 S   | 645 - 770 mm         | 35/24 mm  | PVC/PA 6.6/POM | 150 kg            |
| <b>Mobile QuattroPower entry and exit help with vacuum safety indicator</b>   |                      |           |                |                   |
| 1400261 S   | 860 mm               | 35 mm     | PVC/PA 6.6/POM | 80 kg             |
| 1400262 S   | 980 mm               | 35 mm     | PVC/PA 6.6/POM | 80 kg             |
| 1400263 S   | 740 mm               | 35 mm     | PVC/PA 6.6/POM | 80 kg             |
| 1400264 S   | 850 mm               | 35 mm     | PVC/PA 6.6/POM | 80 kg             |
| <b>QuattroPower supporting handle with vacuum safety indicator</b>            |                      |           |                |                   |
| 1400265 S   | 390 mm               | 35 mm     | PVC/PA 6.6/POM | 80 kg             |
| 1400266 S   | 390 + 120 mm         | 35/35 mm  | PVC/PA 6.6/POM | 80 kg             |
| 1400268 S (Kids)  | 390 mm               | 26 mm     | PVC/PA 6.6/POM | 60 kg             |
| 1400269 S (Kids)  | 390 + 120 mm         | 26/35 mm  | PVC/PA 6.6/POM | 60 kg             |
| <b>Accessories (useable and/or installed in the above mentioned products)</b> |                      |           |                |                   |
| <b>Cardan joint adapter</b>   |                      |           |                |                   |
| 1400559   |                      |           | POM            | 60 kg             |
| <b>Angle joint adapter</b>  |                      |           |                |                   |
| 1400558   |                      |           | POM            | 75 kg             |
| <b>Diagonal joint adapter</b>   |                      |           |                |                   |
| 14400557  |                      |           | Alu/POM        | 120 kg            |

Tested according to: ISO 17966:2016

Production Facility(ies):

043527

TÜV SÜD  
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFICADO ◆ CERTIFICAT